

Requête SQL utiles

Correspondance entre code INSEE présent dans additional_data et cor_area_synthese

Trouver les codes INSEE fournis dans le champ additional_data attribut communeInseeCode, existant dans la table ref_geo.l_areas mais qui ne correspondent pas à ceux présent dans la table gn_synthese.cor_area_synthese :

```
WITH communes AS (
  SELECT la.id_area, la.area_code AS insee_code, la.area_name
  FROM ref_geo.l_areas AS la
  WHERE la.id_type = ref_geo.get_id_area_type_by_code('COM')
  AND la."enable" = TRUE
)
SELECT s.unique_id_sinp, s.the_geom_4326,
s.additional_data::json->>'communeInseeCode' AS code_insee_json, c.area_name
AS area_name_cas, c.insee_code AS code_insee_cas
FROM gn_synthese.synthese AS s
  LEFT JOIN gn_synthese.cor_area_synthese AS cas
  ON (s.id_synthese = cas.id_synthese)
  JOIN communes AS c
  ON (cas.id_area = c.id_area)
WHERE s."precision" IS NULL
  AND s.additional_data::json->>'communeInseeCode' != c.insee_code ;
```

Trouver les codes INSEE fournis dans le champ additional_data attribut communeInseeCode qui ne correspondent pas à ceux présent dans la table gn_synthese.cor_area_synthese car ils n'existent pas dans la table ref_geo.l_areas :

```
WITH communes AS (
  SELECT la.id_area, la.area_code AS insee_code, la.area_name
  FROM ref_geo.l_areas AS la
  WHERE la.id_type = ref_geo.get_id_area_type_by_code('COM')
  AND la."enable" = TRUE
)
SELECT DISTINCT s.additional_data::json->>'communeInseeCode' AS
code_insee_json
FROM gn_synthese.synthese AS s
  LEFT JOIN gn_synthese.cor_area_synthese AS cas
  ON (s.id_synthese = cas.id_synthese)
  JOIN communes AS c
  ON (cas.id_area = c.id_area)
WHERE s."precision" IS NULL
  AND s.additional_data::json->>'communeInseeCode' != c.insee_code
  AND s.additional_data::json->>'communeInseeCode' NOT IN (SELECT
insee_code FROM communes);
```

Calculer le rayon du cercle comprenant un polygone (communes)

```
SELECT
  unique_id_sinp,
  round(radius(ST_MinimumBoundingRadius(la.geom))) AS "precision",
  center(ST_MinimumBoundingRadius(la.geom)) AS rayon,
  ST_MinimumBoundingCircle(la.geom) AS cercle,
  ST_LongestLine(center(ST_MinimumBoundingRadius(la.geom)),
  ST_MinimumBoundingCircle(la.geom)) AS rayon,
  st_centroid(la.geom) AS centroid,
  la.geom,
  la.area_name
FROM gn_synthese.synthese AS s
  LEFT JOIN gn_synthese.cor_area_synthese AS cas
    ON (s.id_synthese = cas.id_synthese)
  JOIN ref_geo.l_areas AS la
    ON (cas.id_area = la.id_area)
WHERE s.id_source != gn_synthese.get_id_source_by_name('SI CBN')
  AND s."precision" IS NULL
  AND la.id_type = ref_geo.get_id_area_type_by_code('COM')
LIMIT 100;
```



From:

<http://sinp-wiki.cbn-alpin.fr/> - **CBNA SINP**

Permanent link:

<http://sinp-wiki.cbn-alpin.fr/database/requetes-sql-utiles?rev=1634134826>

Last update: **2021/10/13 14:20**

