

Installer l'agent Telegraf via Docker

- Se connecter en tant qu'admin : `ssh admin@db-<region>-snp`
- Se placer dans le dossier : `cd ~/docker/telegraf`
 - Lancer le container afin d'afficher les logs : `docker-compose up`
 - Corriger les éventuels problèmes de configuration de Telegraf s'affichant dans les logs
 - Lorsque tout fonctionne correctement, lancer le container en tant que service (option -d) : `docker-compose up -d`

Exemple de fichier de configuration complet

```
# Telegraf Configuration
[global_tags]

[agent]
  interval = "10s"
  round_interval = true
  metric_batch_size = 1000
  metric_buffer_limit = 10000
  collection_jitter = "0s"
  flush_interval = "10s"
  flush_jitter = "0s"
  precision = ""
  hostname = ""
  omit_hostname = false
  # Set to true to debug this config file !
  debug = false

[[outputs.influxdb_v2]]
  urls = ["http://10.0.1.10:8086"]
  ## Token for authentication.
  token = "${INFLUXDB2_TELEGRAF_TOKEN}"
  ## Organization is the name of the organization you wish to write to.
  organization = "${INFLUXDB2_INIT_ORG}"
  ## Destination bucket to write into.
  bucket = "${INFLUXDB2_INIT_BUCKET}"

[[inputs.conntrack]]
  files = ["ip_conntrack_count", "ip_conntrack_max", "nf_conntrack_count", "nf_conntrack_max"]
  dirs =
["/host/proc/sys/net/ipv4/netfilter", "/host/proc/sys/net/netfilter"]

[[inputs.cpu]]
  percpu = true
  totalcpu = true
  collect_cpu_time = false
  report_active = false
```

```
[[inputs.disk]]
  mount_points = ["/host"]
  ignore_fs = ["tmpfs", "devtmpfs", "devfs", "iso9660", "overlay", "aufs",
"squashfs"]

[[inputs.diskio]]
  devices = ["sda"]

[[inputs.docker]]
  endpoint = "unix:///var/run/docker.sock"
  gather_services = false
  container_name_include = []
  container_name_exclude = []
  timeout = "5s"
  perdevice = false
  perdevice_include = ["cpu", "blkio", "network"]
  total_include = ["cpu", "blkio", "network"]
  docker_label_include = []
  docker_label_exclude = []

[[inputs.exec]]
  commands = [
    "cat /opt/srvstatus/status.json"
  ]
  timeout = "5s"
  name_override = "services_stats"
  data_format = "json"
  tag_keys = [
    "service"
  ]

[[inputs.internal]]

[[inputs.interrupts]]
  cpu_as_tag = true
  [inputs.interrupts.tagdrop]
  irq = ["NET_RX", "TASKLET"]

[[inputs.kernel]]

[[inputs.linux_sysctl_fs]]

[[inputs.mem]]

[[inputs.net]]

[[inputs.netstat]]
```

```

[[inputs.nginx]]
  urls = ["http://172.18.5.1:9090/nginx_status"]
  response_timeout = "5s"

[[inputs.nstat]]
  proc_net_netstat = "/host/proc/net/netstat"
  proc_net_snmp = "/host/proc/net/snmp"
  proc_net_snmp6 = "/host/proc/net/snmp6"
  dump_zeros = true

[[inputs.postgresql]]
address = "host=172.18.5.1 user=telegraf password=<password> dbname=postgres
sslmode=disable"
outputaddress="postgresql-floresentinel"
max_lifetime = "0s"
databases = ["geonature2db", "gnatlas"]

[[inputs.processes]]

[[inputs.swap]]

[[inputs.system]]

[[inputs.tail]]
  files = ["/host/var/log/nginx/access.log"]
  data_format = "grok"
  grok_timezone = "Europe/Paris"
  from_beginning = true
  name_override = "nginx_access_log"
  grok_patterns = ["%{CUSTOM_LOG_FORMAT}"]
  # Grock :
https://www.elastic.co/guide/en/logstash/current/plugins-filters-grok.html
  # Grock pattern :
https://github.com/elastic/logstash/blob/v1.4.2/patterns/grok-patterns
  # Ex :
https://github.com/influxdata/telegraf/blob/master/plugins/parsers/grok/influx\_patterns.go
  grok_custom_patterns = ''
    CUSTOM_LOG_FORMAT %{IPORHOST:client_ip} (?:%{NOTSPACE:auth}|-)
(?:%{NOTSPACE:ident}|-) \[%{HTTPDATE:ts}\] "(?:%{WORD:verb}
%{NOTSPACE:request}(?: HTTP/%{NUMBER:http_version:float})?|%{DATA})"
%{NUMBER:resp_code} (?:%{NUMBER:resp_bytes:int}|-) %{QS:referrer}
%{QS:agent} rt="%{NUMBER:request_time:float}"?
uct="(?:%{NUMBER:upstream_connect_time:float}|-)"
uht="(?:%{NUMBER:upstream_header_time:float}|-)"
urt="(?:%{NUMBER:upstream_response_time:float}|-)"
g zr="(?:%{NUMBER:gzip_ratio:float}|-)"
    ''

# WARNING : only for debugging
#[[outputs.file]]

```

Last
update:
2023/05/30 14:22 serveurs:installation:web-srv:docker-telegraf <https://sinp-wiki.cbn-alpin.fr/serveurs/installation/web-srv/docker-telegraf?rev=1685456521>

```
# namepass = ["nginx_access_log"]  
# files = ["/tmp/nginx_access_log.out"]  
# influx_sort_fields = true
```

From:
<https://sinp-wiki.cbn-alpin.fr/> - **CBNA SINP**

Permanent link:
<https://sinp-wiki.cbn-alpin.fr/serveurs/installation/web-srv/docker-telegraf?rev=1685456521>

Last update: **2023/05/30 14:22**

