

Installer l'agent Telegraf via Docker

- Se connecter en tant qu'admin : `ssh admin@db-<region>-snp`
- Se placer dans le dossier : `cd ~/docker/telegraf`
 - Lancer le container afin d'afficher les logs : `docker-compose up`
 - Corriger les éventuels problèmes de configuration de Telegraf s'affichant dans les logs
 - Lorsque tout fonctionne correctement, lancer le container en tant que service (option -d) : `docker-compose up -d`

Monitorer différents services spécifiques

- Nginx:
 - status
 - access log
- PostgreSQL :
- Unicorn : [Doc monitorer Unicorn GeoNature](#)

Exemple de fichier telegraf.conf complet

Exemple avec :

- le support d'InfluxDB v2 accessible sur le port 8086 de l'ip privée 10.0.1.10
- le statut de Nginx sur http://172.18.5.1:9090/nginx_status (voir config Nginx),
- l'analyse des logs de Nginx via Tail et Grok,
- la surveillance de PostgreSQL
- la surveillance des service du système à l'aide du script `srvstatus`
- la surveillance de Unicorn pour GeoNature à l'aide de Statsd

```
# Telegraf Configuration
[global_tags]

[agent]
interval = "10s"
round_interval = true
metric_batch_size = 1000
metric_buffer_limit = 10000
collection_jitter = "0s"
flush_interval = "10s"
flush_jitter = "0s"
precision = ""
hostname = ""
omit_hostname = false
# Set to true to debug this config file !
debug = false

[[outputs.influxdb_v2]]
urls = ["http://10.0.1.10:8086"]
```

```
## Token for authentication.
token = "${INFLUXDB2_TELEGRAF_TOKEN}"
## Organization is the name of the organization you wish to write to.
organization = "${INFLUXDB2_INIT_ORG}"
## Destination bucket to write into.
bucket = "${INFLUXDB2_INIT_BUCKET}"

[[inputs.conntrack]]
  files = ["ip_conntrack_count", "ip_conntrack_max", "nf_conntrack_count",
"nf_conntrack_max"]
  dirs =
["/host/proc/sys/net/ipv4/netfilter", "/host/proc/sys/net/netfilter"]

[[inputs.cpu]]
  percpu = true
  totalcpu = true
  collect_cpu_time = false
  report_active = false

[[inputs.disk]]
  mount_points = ["/host"]
  ignore_fs = ["tmpfs", "devtmpfs", "devfs", "iso9660", "overlay", "aufs",
"squashfs"]

# Monitoring of instance devices
# WARNING : see distinct devices in /dev with `df -h`
[[inputs.diskio]]
  devices = ["sda"]

[[inputs.docker]]
  endpoint = "unix:///var/run/docker.sock"
  gather_services = false
  container_name_include = []
  container_name_exclude = []
  timeout = "5s"
  perdevice = false
  perdevice_include = ["cpu", "blkio", "network"]
  total_include = ["cpu", "blkio", "network"]
  docker_label_include = []
  docker_label_exclude = []

# Monitoring of Systemd services with help of Srvstatus scripts
[[inputs.exec]]
  commands = [
    "cat /opt/srvstatus/status.json"
  ]
  timeout = "5s"
  name_override = "services_stats"
  data_format = "json"
```

```
tag_keys = [
    "service"
]

[[inputs.internal]]

[[inputs.interrupts]]
    cpu_as_tag = true
    [inputs.interrupts.tagdrop]
        irq = ["NET_RX", "TASKLET"]

[[inputs.kernel]]

[[inputs.linux_sysctl_fs]]

[[inputs.mem]]

[[inputs.net]]

[[inputs.netstat]]

# Monitoring of Nginx current status
[[inputs.nginx]]
    urls = ["http://172.18.5.1:9090/nginx_status"]
    response_timeout = "5s"

[[inputs.nstat]]
    proc_net_netstat = "/host/proc/net/netstat"
    proc_net_snmp = "/host/proc/net/snmp"
    proc_net_snmp6 = "/host/proc/net/snmp6"
    dump_zeros = true

[[inputs.postgresql]]
address = "host=172.18.5.1 user=telegraf password=<password> dbname=postgres
sslmode=disable"
outputaddress="postgresql-floresentinelle"
max_lifetime = "0s"
databases = ["geonature2db", "gnatlas"]

[[inputs.processes]]

# Monitoring of Gunicorn for GeoNature, UsersHub, TaxHub and Atlas.
[[inputs.statsd]]
    protocol = "udp"
    max_tcp_connections = 250
    tcp_keep_alive = false
    service_address = ":8125"
    delete_gauges = true
    delete_counters = true
    delete_sets = true
    delete_timings = true
```

```
percentiles = [50.0, 90.0, 99.0, 99.9, 99.95, 100.0]
metric_separator = "_"
parse_data_dog_tags = false
datadog_extensions = false
allowed_pending_messages = 10000
percentile_limit = 1000

[[inputs.swap]]

[[inputs.system]]

# Nginx access log monitoring
[[inputs.tail]]
  files = ["/host/var/log/nginx/access.log"]
  data_format = "grok"
  grok_timezone = "Europe/Paris"
  from_beginning = true
  name_override = "nginx_access_log"
  grok_patterns = ["%{CUSTOM_LOG_FORMAT}"]
  # Grock :
  https://www.elastic.co/guide/en/logstash/current/plugins-filters-grok.html
  # Grock pattern :
  https://github.com/elastic/logstash/blob/v1.4.2/patterns/grok-patterns
  # Ex :
  https://github.com/influxdata/telegraf/blob/master/plugins/parsers/grok/influx_patterns.go
  grok_custom_patterns = '''
    CUSTOM_LOG_FORMAT %{IPORHOST:client_ip} (?:%{NOTSPACE:auth}|-)
    (?:%{NOTSPACE:ident}|-) \[%{HTTPDATE:ts}\] "(?:%{WORD:verb}
    %{NOTSPACE:request}(?: HTTP/%{NUMBER:http_version:float})?|%{DATA})"
    %{NUMBER:resp_code} (?:%{NUMBER:resp_bytes:int}|-) %{QS:referrer}
    %{QS:agent} rt="(?:%{NUMBER:request_time:float})?"
    uct="(?:%{NUMBER:upstream_connect_time:float}|-)"
    uht="(?:%{NUMBER:upstream_header_time:float}|-)"
    urt="(?:%{NUMBER:upstream_response_time:float}|-)"
    gzh="(?:%{NUMBER:gzip_ratio:float}|-)"
    ...

# WARNING : only for debugging
#[[outputs.file]]
# namepass = ["nginx_access_log"]
# files = ["/tmp/nginx_access_log.out"]
# influx_sort_fields = true
```

From:

<https://sinp-wiki.cbn-alpin.fr/> - **CBNA SINP**

Permanent link:

<https://sinp-wiki.cbn-alpin.fr/serveurs/installation/web-srv/docker-telegraf?rev=1685523505>

Last update: **2023/05/31 08:58**

